

Hammond

DUS KOLECTORS

DK-4 Cyclone DusKolector 500 CFM

Height: 54"

Cabinet Model FDK-4 700 CFM



This Cabinet DusKolector has a polyester pleated filter and a dirt pan, as shown on page 3. It is for light and medium intermittent dust sources such as 12" wheel grinders. 22" x 28" x 32" high.

Dust Source inlet
to floor 35"


Cyclone is located in this middle section

For Noise Reducer—see page 10.

Dirt container is located inside door



FLOOR PLAN Top View



SPECIFICATIONS — CFM, Velocity, and Static Pressure are determined by AMCA Test Code Procedures.

Model	Motor	CFM	Velocity FPM	Static Press.	Maximum Collection Capacity				dBA, Slow Response		Inlet Dia.	Outlet Dia.	Dirt Contrn. Cap. Cu.Ft.	Filter or Bag		Net Wt. Lbs.	Ship. Wt. Lbs.
					Grinding (Hard) Wheels	Buffing or Brushing Wheels	Abr. Belts w/Platens (Width)	Abr. Belts w/Contact Wheels (Width)	Without Noise Reducer	With Noise Reducer				No.	Area Sq.Ft.		
FDK-4	½ HP	700	4000	2.0"	Two 12x2"	—	Two 3"	Two 2½"	77	—	Two 4"	—	½	1	8	170	250
DK-4	1HP TEFC	500	5700	4.5"	Two 12x2"	Two 9x2"	Two 3"	One 3"	83	68	4"	7"	1½	1	17	130	220

Electrical Specifications: 230/460 v., 3ph., 60 Hz OR 115/230 v., 1 ph., 60 Hz.